

Automotive Paint Protection Film Care Sheet

We trust that you will enjoy your invisible paint protection. It is designed to prevent premature destruction of your automobile's delicate and valuable paintwork as well as the headlights and foglights. If properly maintained, it has proven itself to be trouble free.

WHAT TO EXPECT IMMEDIATELY AFTER INSTALLATION:

Immediately after installation there may be a small amount of setting solution residue remaining under the film. THIS IS NORMAL and IT WILL DISSIPATE within a short time (depending on temperatures up to a week). DO NOT press on the area with the solution. The look is very similar to the temporary blemishes found with window film application. It looks like streaking or watery bubbles. This is part of the curing process and these visual annoyances will clear up.

Minor variations observed in the material itself will also clear up after time and exposure to the elements. Some cosmetic imperfections, often referred to as "disturbed adhesive" are unavoidable and may make themselves evident as a result of the installation technique necessary to apply to the film.

Your film has been cleaned and waxed so no immediate washing or waxing is required.

CARE (after 72 hours):

- Wash your vehicle as you would normally. Hand washing and waxing once per month is recommended.
- After washing or in between washes apply Plexus plastic cleaner with a clean microfiber towel.
- Wax the film at the same time as the rest of the vehicle (recommended every 3-4 months).
- Remove any foreign material as quickly as possible in order to avoid any staining.
- Never apply a lot of pressure to the films protected surfaces.
- Keep any high pressure washer nozzles at least 36" away from the film edges.

When waxing/polishing, its recommended to overlap the film edge with a 1/4" painters masking tape. This will prevent any wax build-up on the film edge. If tape is not available just simply use an old tooth brush and/or cotton swab dipped in isopropyl (rubbing) alcohol to clean the edge.

DO NOT USE:

Solvent based degreasers
Powder based or abrasive cleaners
High speed rotary buffers
Bug and tar removers
Rubbing compound, clay, or other abrasive material

TNT Window Tinting

7927 Airport Road, Middleton, WI 53562

608.222.TINT (8468)

www.tntwindowtint.com